

AMENDMENT TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.


1. (currently amended): A method of adjusting the brightness of an image, the method comprising the steps of:
acquiring image data by an image acquisition device;
expressing a pixel value of each pixel in said image data as a set of three mutually independent components;
defining the brightness of each pixel based on said three components;
determining a rate of pixels based on a number of pixels having a maximum brightness among all pixels, wherein the maximum brightness among all pixels is taken from a group of commonly encountered brightness; and
automatically making an adjustment to said pixel value based on the rate.

2. (original): The method as set forth in claim 1, wherein said image acquisition device is a digital camera and the adjustment to said image acquisition device is an adjustment to an exposure value at the time of photographing by said digital camera.

3. (original): The method as set forth in claim 2, wherein said pixel value is a value expressed in terms of a linear scale or power scale and wherein the adjustment to said exposure value is made based on the following transformation Eq. (1):

$$\begin{pmatrix} R' \\ G' \\ B' \end{pmatrix} = k \begin{pmatrix} R \\ G \\ B \end{pmatrix} \dots \quad (1)$$

where R' , G' , and B' are the three components after a transformation; R , G , and B are the three components before a transformation; and k is a constant determined according to said rate.

 4. (original): The method as set forth in claim 2, wherein said pixel value is a value expressed in terms of a logarithmic scale and the adjustment to said exposure value is made based on the following transformation Eq. (2):

$$\begin{pmatrix} R' \\ G' \\ B' \end{pmatrix} = \begin{pmatrix} R \\ G \\ B \end{pmatrix} + \begin{pmatrix} k \\ k \\ k \end{pmatrix} \dots \quad (2)$$

where R' , G' , and B' are the three components after a transformation; R , G , and B are the three components before a transformation; and k is a constant determined according to said rate.

5. (original): The method as set forth in claim 1, wherein said image acquisition device is a data acquisition device for acquiring an image as digital data and the adjustment to said pixel value is a data transformation process of transforming the acquired digital data.

Reply to Office Action of September 3, 2003

6. The method as set forth in claim 5, wherein said pixel value is a value expressed in terms of a linear scale or power scale and said data transformation process is a process based on the following transformation Eq. (1):

$$\begin{pmatrix} R' \\ G' \\ B' \end{pmatrix} = k \begin{pmatrix} R \\ G \\ B \end{pmatrix} \dots \quad (1)$$

where R', G', and B' are the three components after a transformation; R, G, and B are the three components before a transformation; and k is a constant determined according to said rate.

7. (original): The method as set forth in claim 5, wherein said pixel value is a value expressed in terms of a logarithmic scale and said data transformation process is a process based on the following transformation Eq. (2):

$$\begin{pmatrix} R' \\ G' \\ B' \end{pmatrix} = \begin{pmatrix} R \\ G \\ B \end{pmatrix} + \begin{pmatrix} k \\ k \\ k \end{pmatrix} \dots \quad (2)$$

where R', G', and B' are the three components after a transformation; R, G, and B are the three components before a transformation; and k is a constant determined according to said rate.

8. (original): The method as set forth in any one of claims 1 through 7, wherein said brightness is defined by the following Eq. (3):

$$L = \max(R, G, B) \quad (3)$$

Cont where L is the brightness of a pixel; R, G, and B are the three components; and $\max(x, y, z)$ is the maximum value among x, y, and z.

9. (currently amended): A digital camera comprising:
image pick-up means for photographing an image and acquiring image data in which a pixel value of each pixel is expressed as a set of three mutually independent components;
brightness analyzing means for computing a histogram of the brightness of said pixel defined based on said three components for said image data acquired by said image pick-up means; and
exposure control means for automatically making an adjustment to an exposure value at the time of photographing on the basis of said histogram so that a rate of pixels based on a number of pixels having a maximum brightness among all pixels becomes a predetermined rate, wherein the maximum brightness among all pixels is taken from a group of commonly encountered brightness.

10. (original): The digital camera as set forth in claim 9, wherein said pixel value is a value expressed in terms of a linear scale or power scale and the adjustment to said exposure value is

made based on the following transformation Eq. (1):

$$\begin{pmatrix} R' \\ G' \\ B' \end{pmatrix} = k \begin{pmatrix} R \\ G \\ B \end{pmatrix} \dots \quad (1)$$

cont
where R', G', and B' are the three components after a transformation; R, G, and B are the three components before a transformation; and k is a constant determined according to said rate.

11. (original): The digital camera as set forth in claim 9, wherein said pixel value is a value expressed in terms of a logarithmic scale and the adjustment to said exposure value is made based on the following transformation Eq. (2):

$$\begin{pmatrix} R' \\ G' \\ B' \end{pmatrix} = \begin{pmatrix} R \\ G \\ B \end{pmatrix} + \begin{pmatrix} k \\ k \\ k \end{pmatrix} \dots \quad (2)$$

where R', G', and B' are the three components after a transformation; R, G, and B are the three components before a transformation; and k is a constant determined according to said rate.

12. (original): The digital camera as set forth in any one of claims 9 through 11, wherein said brightness is defined by the following Eq. (3):

$$L = \max(R, G, B) \quad (3)$$

where L is the brightness of a pixel; R, G, and B are the three components; and $\max(x, y, z)$ is the maximum value among x, y, and z.

13. (currently amended) An image processor comprising:

data acquisition means for acquiring an image as digital data in which a pixel value of each pixel is expressed as a set of three mutually independent components;

brightness analyzing means for computing a histogram of the brightness of said pixel defined based on said three components for said digital data acquired by said data acquisition means; and

data transformation means for automatically performing a data transformation process on the acquired digital data on the basis of said histogram so that a rate of pixels based on a number of pixels having a maximum brightness among all pixels is made a predetermined rate, wherein the maximum brightness among all pixels is taken from a group of commonly encountered brightness.

14. (original): The image processor as set forth in claim 13, wherein said pixel value is a value expressed in terms of a linear scale or power scale and said data transformation process is process based on the following transformation Eq. (1):

$$\begin{pmatrix} R' \\ G' \\ B' \end{pmatrix} = k \begin{pmatrix} R \\ G \\ B \end{pmatrix} \dots \quad (1)$$

where R', G', and B' are the three components after a transformation; R, G, and B are the three components before a transformation; and k is a constant determined according to said rate.

15. (original): The image processor as set forth in claim 13, wherein said pixel value is a value expressed in terms of a logarithmic scale and said data transformation process is a process based on the following transformation Eq. (2):

$$\begin{pmatrix} R' \\ G' \\ B' \end{pmatrix} = \begin{pmatrix} R \\ G \\ B \end{pmatrix} + \begin{pmatrix} k \\ k \\ k \end{pmatrix} \dots \quad (2)$$

where R', G', and B' are the three components after a transformation; R, G, and B are the three components before a transformation; and k is a constant determined according to said rate.

16. (original): The image processor as set forth in any one of claims 13 through 15, wherein said brightness is defined by the following Eq. (3):

$$L = \max(R, G, B) \quad (3)$$

where L is the brightness of a pixel; R, G, and B are the three components; and $\max(x, y, z)$ is the maximum value among x, y, and z.

17. (currently amended) A method of adjusting the brightness of an image, the method comprising the steps of:

acquiring image data by an image acquisition device;
expressing a pixel value of each pixel in said image data as a chrominance value;

defining the brightness of each pixel based on said chrominance value;

determining a rate of pixels based on a number of pixels having a maximum brightness among all pixels, wherein the maximum brightness among all pixels is taken from a group of commonly encountered brightness; and

automatically making an adjustment to said pixel value based on the rate.

18. (currently amended) A digital camera comprising:

image pick-up means for photographing an image and acquiring image data in which a pixel value of each pixel is expressed as a chrominance value;

brightness analyzing means for computing a histogram of the brightness of said pixel defined based on said chrominance value for said image data acquired by said image pick-up means; and

exposure control means for automatically making an adjustment to an exposure value at the time of photographing on the

basis of said histogram so that a rate of pixels based on a number of pixels having a maximum brightness among all pixels becomes a predetermined rate, wherein the maximum brightness among all pixels is taken from a group of commonly encountered brightness.

19. (currently amended) An image processor comprising:

of
and
data acquisition means for acquiring an image as digital data in which a pixel value of each pixel is expressed as a chrominance value;

brightness analyzing means for computing a histogram of the brightness of said pixel defined based on said chrominance value for said digital data acquired by said data acquisition means; and

data transformation means for automatically performing a data transformation process on the acquired digital data on the basis of said histogram so that a rate of pixels based on a number of pixels having a maximum brightness among all pixels is made a predetermined rate, wherein the maximum brightness among all pixels is taken from a group of commonly encountered brightness.
